



SEALED CHAMBER GAS WATER HEATER UAN



High DHW output



No pilot flame



Multifunctional touch display



Closed chamber



Gas and temperature sensor



Multiple protection



Gas pipeline (C12, C32)



Class 6 NOx

| MODEL | | HTW-CLE-11NOXUA2GN | HTW-CLE-11NOXUA2GLP | HTW-CLE-11NOXUA2GLP* |
|------------------------------|-------------------|---------------------------|--------------------------|--------------------------|
| EAN CODE | | 8435483848702 | 8435483848719 | 8435483830745 |
| Power supply | V, F, Hz | 220-240V (1 Phase ~ 50Hz) | | |
| POWER | | | | |
| Input power | kW | 22 | 22 | 22 |
| Useful power | kW | 19,2 | 19,2 | 19,4 |
| Min. Input power | kW | 9,5 | 9,5 | 10,8 |
| Min. Output power | kW | 8,2 | 7 | 9,5 |
| Performance | % | 77,24 | 77,24 | 85 |
| Declared Profile | — | M | M | M |
| Energy classification | — | A | A | A |
| PERFORMANCE | | | | |
| Gas type | — | Natural G20 | Butane G30 / Propane G31 | Butane G30 / Propane G31 |
| Combustion | — | Closed chamber | Closed chamber | Closed chamber |
| Gas pressure | mbar | 20 | 28 - 30 / 37 | 28 - 30 / 37 |
| Maximum gas consumption | m ³ /h | 2,36 | 0,68/0,89 | 0,68/0,89 |
| NOx emission | mg/kWh | 38,13 | 54,5 | 45 |
| FEATURES | | | | |
| Maximum pressure | bar | 10 | 10 | 10 |
| Minimum pressure | bar | 0,2 | 0,2 | 0,2 |
| Flow rate (2BAR) | L/min | 11 | 11 | 11 |
| Minimum flow (2BAR) | L/min | 8 | 8 | 8 |
| Water temperature | °C | 35 ~ 65 | 35 ~ 65 | 30 ~ 60 |
| Sound level | dB | 60 | 60 | 60 |
| DIMENSIONS AND WEIGHT | | | | |
| Net dimensions (W × H × D) | mm | 372×663×223 | 372×663×223 | 370×660×213 |
| Gross dimensions (W × H × D) | mm | 435×800×280 | 435×800×280 | 435×800×280 |
| Net weight | kg | 12,25 | 12,25 | 14,5 |
| Gross weight | kg | 13,85 | 13,85 | 16,4 |
| CONNECTIONS | | | | |
| Gas connection | in. | 1/2" | 1/2" | 1/2" |
| Cold water connection | in. | 1/2" | 1/2" | 1/2" |
| Hot water connection | in. | 1/2" | 1/2" | 1/2" |
| Ø Gas outlet | mm | Ø60/100 | Ø60/100 | Ø60/100 |
| Max. gas outlet length | m | 4 | 4 | 4 |

*Until end of stock