



## FANCOIL INDOOR UNIT COMPACT CASSETTE MKD



MODELS		HTW-MKD-V400	HTW-MKD-V500
EAN CODE		8435483820425	8435483820395
Power Supply		V, P, HZ	220-240V (1 Phase ~ 50Hz)
<b>PERFORMANCE</b>			
Cooling capacity <sup>1</sup>	Capacity (H/M/L)	<b>kW</b>	3,96/3,26/2,76
	Consumption (H/M/L)	<b>W</b>	28/19/15
Heating capacity <sup>2</sup>	Capacity (H/M/L)	<b>kW</b>	5,4/4,34/3,57
	Consumption (H/M/L)	<b>W</b>	28/16/10
<b>FEATURES</b>			
Sound pressure		<b>dB(A)</b>	42/36/30
Water flow (H/M/L)		<b>m³/h</b>	0,7/0,58/0,51
Air flow (H/M/L)		<b>m³/h</b>	719/561/448
Hot water pressure drop (H/M/L)		<b>kPa</b>	12,68/6,4/4,92
<b>DIMENSIONS AND WEIGHT</b>			
Indoor unit/panel	Net dimensions (WxHxD)	<b>mm</b>	575x261x575 / 647x50x647
	Net weight	<b>Kg</b>	16,5 / 2,5
<b>CONNECTIONS</b>			
Pipeline	Water inlet and outlet	<b>in.</b>	3/4"
	Drainage	<b>mm</b>	25 Ø

HTW reserves all rights to modify models and technical data without prior notice. Valid information except typographical or printing error.

**Notes:**

H: High fan speed; M: Average fan speed; L: Low fan speed.

1. Cold mode: Air inlet temperature 27°C BS / 19°C BH; Water inlet / outlet temperature 7°C / 12°C.

2. Heat mode: Air inlet temperature 20°C BH; Water inlet temperature 50°C; Water flow the same as in cold mode.