

HTW

QUALITY COMFORT EVERYWHERE

HOME RANGE IX21D5

3 YEARS WARRANTY TOTAL
QUALITY COMMITMENT

10 YEARS WARRANTY COMPRESSOR
QUALITY COMMITMENT

21dB
SEGUN MODELO

A++
SEER

A+
SCOP

A+++
SCOP Warmer

Enjoy of comfort

With the IX21D5 split you will be able to live the best comfort, with its triple filter you will eliminate bad odors and small particles, also thanks to its included Wi-Fi you will be able to control all the functions wherever you are.



TRIPLE FILTER

10 YEARS WARRANTY COMPRESSOR



Clean Air

Includes Cold Catalyst, Silver Ion and Activated Carbon filters to eliminate bad odors and particles.




Wi-Fi Included

You can control the equipment from a smartphone, tablet or by voice with Alexa and Google Home.

CONNECTA+

Optional Conecta+

Special plate for automatic ON/OFF switching of the air conditioning in hotel cards, tourist flats or window sensors.



Versatility

Soporta grandes distancias de instalación: 50 m de distancia y 25 m de desnivel (para el modelo 7,1 kW).



Service life

The coils of the indoor and outdoor unit have Golden Fin protection, an anticorrosive for saline environments that extends their durability.



Comfort

With the "I Feel" function, the split takes as the reference temperature of the room the one with the remote control.



Efficient

Energy classification A+++ in cooling and A+++ in heating for hot areas.

10 YEARS WARRANTY
COMPRESSOR



TRIPLE FILTER

**SPLIT 1X1
IX21D5**

CONNECTA+
Optional



R-32

DC inverter



		HTWS026IX21D5-R32	HTWS035IX21D5-R32	HTWS052IX21D5-R32	HTWS071IX21D5-R32
MODEL	INT.	HTWS026IX21D5-R32-I	HTWS035IX21D5-R32-I	HTWS052IX21D5-R32-I	HTWS071IX21D5-R32-I
	EXT.	HTWS026IX21D5-R32-O	HTWS035IX21D5-R32-O	HTWS052IX21D5-R32-O	HTWS071IX21D5-R32-O
EAN CODE		8435483854048	8435483854079	8435483854352	8435483854383
Power supply	V,F,HZ	220-240V (1 Phase- 50Hz) / Exterior Unit			

PERFORMANCE

		HTWS026IX21D5-R32	HTWS035IX21D5-R32	HTWS052IX21D5-R32	HTWS071IX21D5-R32
Cooling capacity	Capacity	kW 2,64 (1,00-3,40)	3,5 (1,11-3,92)	5,28 (1,99-6,73)	7,03 (2,08-7,92)
		Btu/h 9.000 (3.100-11.600)	12.000 (3.800-13.400)	18.100 (6.800-2.300)	23.900 (7.100-27.000)
	Consumption	W 800(100-1240)	1320(83-1600)	1550 (140-2300)	2600 (420-3150)
	Current	A 3,48	5,8	6,7	11,5
	SEER	W/W 7	6,5	7,4	6,1
	Energy class	Cold A++	A++	A++	A++
Annual consumption	kWh 130	188	247	405	
Heating capacity	Capacity	kW 2,93 (0,84-3,37)	3,81 (1,09-4,17)	5,57 (1,29-6,74)	7,33 (1,62-7,92)
		Btu/h 10.000 (2.800-11.500)	13.000 (3.700-14.200)	18.800 (4.400-23.000)	24.900 (5.500-27.000)
	Consumption	W 930 (120-1.200)	1.190 (167-1.400)	1.570 (220-2350)	2.400 (300-2.750)
	Current	A 4,05	5,3	6,8	11
	SCOP	W/W 4,1	4,1	4,0	4,0
	Energy class	heat A+	A+	A+	A+
Annual consumption	kWh 792	957	1435	1680	

CHARACTERISTICS

		HTWS026IX21D5-R32	HTWS035IX21D5-R32	HTWS052IX21D5-R32	HTWS071IX21D5-R32
Indoor unit	Sound power (H/M/L/S)	dB(A) 50	54	56	59
	Sound pressure (H/M/L/S)	dB(A) 37/32/25/21,5	39,5/35,5/25/21,5	42,5/36/26/20	45/40,5/36/29,5
	Air flow (H/M/L/S)	m3/h 435/333/259	530/430/310	840/680/540	980/817/662
	Temperature range	°C 17-32/0-30	17-32/0-30	17-32/0-30	17-32/0-30
Outdoor unit	Sound power	dB(A) 59	64	63	67
	Sound pressure	dB(A) 55	55	56	59
	Air flow	m3/h 1750	1750	2100	3500
	Operating temperature	°C -15-50/-20-30	-15-50/-20-30	-15-50/-20-30	-15-50/-20-30
Refrigerant	Compressor	Type ROTARY	ROTARY	Rotary	Twin-rotary
		Brand GMCC	GMCC	GMCC	GMCC
	Type/Charge	R32/Kg 0,47	0,52	1,08	1,42
	Carga adicional	g/m 12	12	12	24

DIMENSIONS AND WEIGHT

		HTWS026IX21D5-R32	HTWS035IX21D5-R32	HTWS052IX21D5-R32	HTWS071IX21D5-R32
Indoor unit	Net dimensions (W×H×D)	mm 715x194x285	805x194x285	957x302x213	1040x327x220
	Gross dimensions (W×H×D)	mm 780x270x365	870x270x365	1035x385x295	1120x405x315
	Net/Gross weight	Kg 6,7/8,8	7,3/9,5	10/13	12,3/15,8
Outdoor unit	Net dimensions (W×H×D)	mm 720x270x495	720x270x495	805x554x330	890x673x342
	Gross dimensions (W×H×D)	mm 835x300x540	835x300x540	915x615x370	995x740x398
	Net/Gross weight	Kg 21/22,8	21/22,8	32,7/35,4	42,9/45,9

CONNECTIONS

		HTWS026IX21D5-R32	HTWS035IX21D5-R32	HTWS052IX21D5-R32	HTWS071IX21D5-R32
Refrigeration pipe	Liquid - Gas	Pulg. 1/4-3/8	1/4-3/8	1/4-1/2	3/8-5/8
	Max. length	m 25	25	30	50
	Max. elevation	m 10	10	20	25
Electric connections	Power supply	mm 2x2,5+T	2x2,5+T	2x2,5+T	2x2,5+T
	Interconnection	mm 4x2,5+T	4x2,5+T	4x2,5+T	4x2,5+T

Notes:

Capacity data in standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.
The dimensions of the electrical wiring are approximate, they should be calculated according to the conditions of the installation itself.