

# HTW

QUALITY COMFORT EVERYWHERE

## IX39B5

**3 YEARS WARRANTY TOTAL**  
QUALITY COMMITMENT

**10 YEARS WARRANTY COMPRESSOR**  
QUALITY COMMITMENT

**21dB**  
SEGUN MODELO

**A++**  
SEER

**A+**  
SCOP

**A+++**  
SCOP Warmer

## Enjoy of comfort

With the IX39B5 split you will be able to live the best comfort, with its triple filter you will eliminate bad odors and small particles, also thanks to its included Wi-Fi you will be able to control all the functions wherever you are.



**TRIPLE FILTER**

**10 YEARS WARRANTY COMPRESSOR**



### Clean Air

Includes Cold Catalyst, Silver Ion and Activated Carbon filters to eliminate bad odors and particles.




### Wi-Fi Included

You can control the equipment from a smartphone, tablet or by voice with Alexa and Google Home.

**CONNECTA+**

### Optional Conecta+

Special plate for automatic ON/OFF switching of the air conditioning in hotel cards, tourist flats or window sensors.



### Versatility

Soporta grandes distancias de instalación: 50 m de distancia y 25 m de desnivel (para el modelo 7,1 kW).



### Service life

The coils of the indoor and outdoor unit have Golden Fin protection, an anticorrosive for saline environments that extends their durability.



### Comfort

With the "I Feel" function, the split takes as the reference temperature of the room the one with the remote control.



### Efficient

Energy classification A++ in cooling and A+++ in heating for hot areas.

# HTW

QUALITY COMFORT EVERYWHERE

## HOME RANGE

**3 YEARS WARRANTY TOTAL**  
QUALITY COMMITMENT

**10 YEARS WARRANTY COMPRESSOR**  
QUALITY COMMITMENT

**21dB**  
DEPENDS ON MODEL

**A++ SEER**

**A+ SCOP**

**A+++ SCOP Warmer**

**10 YEARS WARRANTY COMPRESSOR**



**WIFI INCLUDED**

**SPLIT 1X1 IX39B5**

**CONNECTA+ Optional**



MODELS	INT.	HTWS026IX39B5-R32-I	HTWS035IX39B5-R32-I	HTWS052IX39B5-R32-I	HTWS071IX39B5-R32-I
	EXT.	HTWS026IX39B5-R32-O	HTWS035IX39B5-R32-O	HTWS052IX39B5-R32-O	HTWS071IX39B5-R32-O
EAN CODE		8435483854130	8435483854109	8435483854291	8435483854321
Electrical power supply	<b>V,F,Hz</b>	220~240V (1 Phase ~ 50Hz) / Outdoor unit			

### PERFORMANCE

		HTWS026IX39B5-R32	HTWS035IX39B5-R32	HTWS052IX39B5-R32	HTWS071IX39B5-R32	
Cooling capacity	Capacity	<b>kW</b> 2,64 (1,00-3,40)	3,5 (1,11-3,92)	5,28 (1,99-6,73)	7,03 (2,08-7,92)	
		<b>Btu/h</b> 9.000 (3.100-11.600)	12.000 (3.800-13.400)	18.100 (6.800-2.300)	23.900 (7.100-27.000)	
	Consumption	<b>W</b> 800(100-1240)	1320(83-1600)	1550 (140-2300)	2600 (420-3150)	
	Current	<b>A</b> 3,48	5,8	6,7	11,5	
	SEER	<b>W/W</b> 7	6,5	7,4	6,1	
	Energy class	<b>Frio</b>	A++	A++	A++	A++
	Annual consumption	<b>kWh</b>	130	188	247	405
Heating capacity	Capacity	<b>kW</b> 2,93 (0,84-3,37)	3,81 (1,09-4,17)	5,57 (1,29-6,74)	7,33 (1,62-7,92)	
		<b>Btu/h</b> 10.000 (2.800-11.500)	13.000 (3.700-14.200)	18.800 (4.400-23.000)	24.900 (5.500-27.000)	
	Consumption	<b>W</b> 930 (120-1.200)	1.190 (167-1.400)	1.570 (220-2350)	2.400 (300-2.750)	
	Current	<b>A</b> 4,05	5,3	6,8	11	
	SCOP	<b>W/W</b> 4,1	4,1	4,0	4,0	
	Energy class	<b>Calor</b>	A+	A+	A+	A+
	Annual consumption	<b>kWh</b>	792	957	1435	1680

### FEATURES

		HTWS026IX39B5-R32	HTWS035IX39B5-R32	HTWS052IX39B5-R32	HTWS071IX39B5-R32
Indoor unit	Sound power (H/M/L/S)	<b>dB</b> 50	54	56	59
	Sound pressure (H/M/L/S)	<b>dB</b> 37/32/25/21,5	39,5/35,5/25/21,5	42,5/36/26/20	45/40,5/36/29,5
	Air flow (H/M/L/S)	<b>m³/h</b> 435/333/259	530/430/310	840/680/540	980/817/662
	Temperature range	<b>°C</b> 17-32/0-30	17-32/0-30	17-32/0-30	17-32/0-30
Outdoor unit	Sound power	<b>dB</b> 59	64	63	67
	Sound pressure	<b>dB</b> 55	55	56	59
	Air flow	<b>m³/h</b> 1750	1750	2100	3500
	Operating temperature	<b>°C</b> -15-50/-20-30	-15-50/-20-30	-15-50/-20-30	-15-50/-20-30
Refrigerant	Compressor	<b>Type</b> ROTARY	ROTARY	Rotary	Twin-rotary
		<b>Brand</b> GMCC	GMCC	GMCC	GMCC
	Type/Charge	<b>R32/kg</b> 0,47	0,52	1,08	1,42
	Carga adicional	<b>g/m</b> 12	12	12	24

### DIMENSIONS AND WEIGHT

		HTWS026IX39B5-R32	HTWS035IX39B5-R32	HTWS052IX39B5-R32	HTWS071IX39B5-R32
Indoor unit	Net dimensions (WxHxD)	<b>mm</b> 715x194x285	805x194x285	957x302x213	1040x327x220
	Gross dimensions (WxHxD)	<b>mm</b> 780x270x365	870x270x365	1035x385x295	1120x405x315
	Net/Gross weight	<b>kg</b> 6,7/8,8	7,3/9,5	10/13	12,3/15,8
Outdoor unit	Net dimensions (WxHxD)	<b>mm</b> 720x270x495	720x270x495	805x554x330	890x673x342
	Gross dimensions (WxHxD)	<b>mm</b> 835x300x540	835x300x540	915x615x370	995x740x398
	Net/Gross weight	<b>kg</b> 21/22,8	21/22,8	32,7/35,4	42,9/45,9

### CONNECTIONS

		HTWS026IX39B5-R32	HTWS035IX39B5-R32	HTWS052IX39B5-R32	HTWS071IX39B5-R32
Refrigeration pipe	Liquid - Gas	<b>in.</b> 1/4-3/8	1/4-3/8	1/4-1/2	3/8-5/8
	Max. length	<b>m</b> 25	25	30	50
	Max. elevation	<b>m</b> 10	10	20	25
Electric connections	Power supply	<b>mm</b> 2x2,5+T	2x2,5+T	2x2,5+T	2x2,5+T
	Interconnection	<b>mm</b> 4x2,5+T	4x2,5+T	4x2,5+T	4x2,5+T

#### Notes:

Capacity data in standard conditions. Actual data will vary depending on where the equipment is installed and how it is used. The dimensions of the electrical wiring are approximate, they should be calculated according to the conditions of the installation itself.