

## **AQUA RANGE**









## VERTICAL ELECTRIC WATER HEATER

## **ESSENTIAL HIDE**















Adjustable temperature

High density polyurethane insulation

Electrolyti sleeves

Magnesium anticorrosive anode

nesium Dry powder prrosive enamelled tank node

Submerg

protection

MODEL		HTW-TV-15ESSHIDE	HTW-TV-30ESSHIDE
EAN CODE		8435483863019	8435483863026
Electrical power supply	V, F, Hz	220-240V (1 Phase ~ 50Hz)	
		POWER	
Power	W	1500	1500
Current	A	6,5	6,5
Declared profile	-	S	S
Energy classification	-	В	С
		PERFORMANCE	
Capacity	L	15	30
Maximum working pressure	Мра	0,75	0,75
Operation temperature	°C	5~50	5~50
Recovery time 15 - 40°C	min	19	33
Annual electricity consumption	kWh	487,8	537
		FEATURES	
Insulation thickness	mm	20	20
Insulation layer material	-	Polyurethane	Polyurethane
Material thickness	mm	1,6	2
Coating type	-	Dry powder enamel	
Protection degree	-	IPx4	IPx4
Anode	Туре	Magnesium	Magnesium
Resistance	Туре	Submerged	Submerged
Installation type	-	Undermount vertical sink	Undermount vertical sink
Water inlet pipe	In.	1/2"	1/2"
		DIMENSIONS AND WEIGHT	
Net dimensions (W×H×D)	mm	380x380x325	440x440x390
Gross dimensions (W×H×D)	mm	440x430x385	500x490x445
Net weight	kg	8	12,2
Gross weight	kg	9,8	14,2

<sup>\*5</sup> years warranty on the tank (by performing the required maintenance)