

HTW

QUALITY COMFORT EVERYWHERE

AQUA RANGE | ELECTRIC WATER HEATER SMART PLUS



Speed, comfort and efficiency at your fingertips.

Speed, comfort and efficiency at your fingertips: Smart Plus thermoses have the best advances in technology. Thanks to the Smart system, it performs a continuous and automatic temperature adjustment and learns from consumption cycles, adapting to the user's usage patterns, achieving greater energy savings. Thanks to its WIFI connectivity, you can also access control of the functions of the thermos wherever you are.




Wi-Fi monitoring

Control of the thermos from a smartphone or tablet even if the user is not at home.



Smart Mode

HTW Smart Plus automatically adapts to the habits of each user, achieving a precise temperature based on actual demand.



Electronic Anode

The electronic anode does not require maintenance, resulting in greater protection against corrosion during the useful life of the water heater.



High energy efficiency

The ECO system allows the water heater to work in saving mode, consuming less energy.



Anti-Bacteria

Through a sterilization system, this function achieves pathogen-free water and zero risk of infection.



Notification Ready

The thermos makes a warning when the desired temperature is reached, achieving greater economic savings and better energy efficiency.



Timer

Allows you to program the time of operation and the exact temperature of the water, optimizing consumption.



Ease of installation

Easy and simple installation thanks to the anchoring system and the simple connection to an electrical outlet.



ELECTRONIC ANODE
LOW MAINTENANCE

VERTICAL ELECTRIC WATER HEATER SMART PLUS



Smart Mode

Resistance
Incoloy 840

High density
polymethane
insulation

Electronic
anode

Dry overheating
protection

Anti-bacterial

Anti-freeze

MODEL		HTW-TV-030SMPLUS	HTW-TV-050SMPLUS	HTW-TV-080SMPLUS	HTW-TV-100SMPLUS
EAN CODE		8435483836389	8435483836396	8435483836402	8435483836419
Power Supply	V,F,Hz	220-240V (1 Phase ~ 50/60Hz)			
POWER					
Power	W	2000	2000	2000	2000
Current	A	8,3-9,1	8,3-9,1	8,3-9,1	8,3-9,1
Declared profile	-	S	M	M	M
Energy class	-	B	B	B	B
PERFORMANCE					
Capacity	L	30	50	80	100
Maximun working pressure	MPa	0,75	0,75	0,75	0,75
Operating temperature	°C	30~75	30~75	30~75	30~75
Recovery time 15~40°C	min	26	43	69	87
Consumo anual de electricidad	kWh	521,3	1261,3	1259,9	1301,8
FEATURES					
Insulation thickness	mm	25	25	25	25
Material de la capa de aislamiento	-	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Material thickness	mm	1,5	1,8	1,8	1,8
Coating type	-	Electrostatic Dry Powder Enamel			
Degree of protection	-	IPX4	IPX4	IPX4	IPX4
Anode	Type	Electronic	Electronic	Electronic	Electronic
Resistance	-	Incoloy 840	Incoloy 840	Incoloy 840	Incoloy 840
Installation type	-	Vertical	Vertical	Vertical	Vertical
Water inlet pipe	in.	1/2"	1/2"	1/2"	1/2"
DIMENSIONS AND WEIGHT					
Net dimensions (ØxH)	mm	Ø350x655	Ø390x778	Ø460x848	Ø460x1003
Gross dimensions	mm	410x700x410	465x845x465	545x888x545	545x1043x545
Net weight	kg	13,8	17,1	23,7	28,7
Gross weight	kg	15,5	19,7	26,5	31,9

*5 years warranty on tank
(performing the required maintenance)