



OPEN CHAMBER GAS WATER HEATER OBI 2



High ACS
production



Flameless pilot



Super slim



LED Display



Gas and
temperature
sensor



Multiple protection



Class 6 NOx

MODELS

EAN CODE		8435483849563	8435483849556
Power Supply	V, F, Hz	DC 3V (2x batteries type D 1.5V R20P)	
POWER			
Input power	kW	22	22
Useful power	kW	19,4	19,4
Minimum input power	kW	7,5	7,5
Minimum output power	kW	6,8	6,8
Performance	%	79	79
Declared profile	—	M	M
Energy classification	—	A	A
PERFORMANCE			
Gas type	—	Butane G30 / Propane G31	Natural G20
Combustion	—	Open chamber	Open Chamber
Gas pressure	mbar	29/37	20
Maximum gas consumption	m³/h	0,68/0,89	2,36
NOx emission	mg/kWh	45	27
HEATER TYPE			
Maximum pressure	bar	10	10
Minimum pressure	bar	0,3	0,3
Maximum flow (2BAR)	L/min	11	11
Minimum flow (2BAR)	L/min	5	5
Water temperature	°C	30~85	30~85
Sound level	dB	62	62
DIMENSIONS AND WEIGHT			
Net dimensions (WxHxD)	mm	330x629x213	330x629x213
Gross dimensions (WxHxD)	mm	400x740x300	400x740x300
Net weight	kg	10,1	10,1
Gross weight	kg	11,8	11,8
CONNECTIONS			
Gas connection	Inch	1/2"	1/2"
Cold water connection	Inch	1/2"	1/2"
Hot water connection	Inch	1/2"	1/2"
Ø Gas exhauster	mm	Ø 110	Ø 110