

## GAMME OFFICE | QUATTRO CASSETTE

# ADMIRA PLUS

A++  
SEER

A+  
SCOP

A+++  
SCOP  
Warmer

## Aesthetics and comfort: more cost-efficiency

The HTW Admira Plus cassette series has been specially designed for commercial use. With 360° air distribution and a slim and attractive design, they provide pleasant thermal comfort as well as perfect integration into any modular ceiling. Ideal for commercial premises, offices, hotels, etc.



10 YEARS  
WARRANTY  
COMPRESSOR



### New design

The new cassette panel allows better air distribution over 360°.



### More comfort

The fan speed can be adjusted in percentages from 1% to 100% to make it easier to adjust the airflow according to our thermal sensation.



### Condensated pump

Including condensate pump with 750 mm lift.



### Efficiency

A++ rating in cooling and A+++ in heating for warm areas.



### WiFi included

With the included WiFi, you can control the device from a smartphone, tablet or by voice with Alexa and Google Home.



### Golden Fin

This coating is applied to the indoor and outdoor unit coils providing protection against corrosion from saline environments.



### ON/OFF contacts and alarm

These can be used to install door or window contacts, hotel card holders or to connect fire alarms.



### Slim design

The height of the ducts is reduced in order to be able to adapt to installations where space is limited.



## QUATTRO CASSETTE ADMIRA PLUS



Wifi  
included

Independent  
vane control  
60x60

DC Inverter  
compressor  
and fan

GOLDEN FIN  
Protection

I feel  
function

Condensate  
pump

Stop/start  
contact and  
alarm

Remote control  
included

24h  
programming

| MODEL                     |                               | 4x I.U.            | HTW-4C6105ADM2R32T3W                    | HTW-4C6140ADM2R32T3W |
|---------------------------|-------------------------------|--------------------|---|----------------------|
|                           |                               | PANEL              | HTW-C6I-026ADM2R32WF                    | HTW-C6I-035ADM2R32WF |
|                           |                               | O.U.               | HTW-C6PV-ADM2R32                        | HTW-C6PV-ADM2R32     |
|                           |                               |                    | HTW-UOT3-140ADM2R32                     | HTW-UOT3-140ADM2R32  |
| EAN CODE                  |                               |                    | 8435483863613                           | 8435483857995        |
| Power supply / Connection |                               | V, P, Hz           | 380-415V (3 Phase~ 50Hz) / Outdoor unit |                      |
| PERFORMANCE               |                               |                    |   |                      |
| Cooling capacity          | kW                            | 10,5 (2,70~11,43)  |   | 14 (3,52~15,83)      |
|                           | Btu/h                         | 36000 (9200~39000) |   | 48000 (12000~54000)  |
| SEER                      | W/W                           | 6,7                |   | 6,1                  |
| Energy class              | Cold                          | A++                |   | A++                  |
| Heating capacity          | kW                            | 11,64 (2,78~12,30) |   | 16,12 (4,10~17,29)   |
|                           | Btu/h                         | 38000 (9500~42000) |   | 55000 (14000~59000)  |
| SCOP                      | W/W                           | 4,0                |   | 4,0                  |
| Energy class              | Heat                          | A+                 |   | A+                   |
| CHARACTERISTICS           |                               |                    |   |                      |
| Indoor unit               | Sound power                   | dB(A)              | 55                                      |                      |
|                           | Sound pressure                | dB(A)              | 40/37/34                                |                      |
|                           | Air flow (H/M/L/S)            | m³/h               | 500/460/400                             |                      |
|                           | Independent slat control      | -                  | Yes                                     |                      |
| Unit outdoor              | Sound power                   | dB(A)              | 70                                      |                      |
|                           | Sound pressure                | dB(A)              | 63                                      |                      |
|                           | Air flow                      | m³/h               | 4000                                    |                      |
|                           | Compressor                    | -                  | GMCC                                    |                      |
|                           | Temp. cool/heat operation     | °C                 | -15~50 / -20~24                         |                      |
| Refrigerant               | Type / Load                   | R32/Kg             | 2,90                                    |                      |
|                           | Additional load > 5 m         | g/m                | 24                                      |                      |
| DIMENSIONS AND WEIGHT     |                               |                    |   |                      |
| Indoor unit               | Dim. net cassette (WxHxD)     | mm                 | 570x245x570                             |                      |
|                           | Dim. gross cassette (WxHxD)   | mm                 | 715x295x640                             |                      |
|                           | Dim. net panel (WxHxD)        | mm                 | 620x50x620                              |                      |
|                           | Dim. gross panel (WxHxD)      | mm                 | 715x115x700                             |                      |
|                           | Net / Gross weight (cassette) | kg                 | 16,1/18,8                               |                      |
|                           | Net / gross weight (panel)    | mm                 | 2,7/4,3                                 |                      |
| Unit outdoor              | Net dimensions (WxHxD)        | mm                 | 975x980x375                             |                      |
|                           | Gross dimensions (WxHxD)      | mm                 | 1080x1145x500                           |                      |
|                           | Net / gross weight            | Kg                 | 90/105                                  |                      |
| CONNECTIONS               |                               |                    |   |                      |
| Refrigeration piping      | Liquid - Gas                  | In.                | 3/8" - 5/8"                             |                      |
|                           | Max. length.                  | m                  | 75                                      |                      |
|                           | Max. level.                   | m                  | 30                                      |                      |
| Electrical connections    | External supply               | mm                 | 4 x 6 + T                               |                      |
|                           | Interconnection               | mm                 | 3 x 1.5 + T                             |                      |