

HOME RANGE | CONSOLE 1x1

INSPIRA

3 YEARS
WARRANTY
TOTAL
QUALITY COMMITMENT

5 YEARS
WARRANTY
COMPRESSOR
QUALITY COMMITMENT

A++
SEER
A+
SCOP

Greater comfort for large areas

The HTW Inspira floor console stands out for its efficiency class A++ and for its comfort thanks to the fan speed adjustment. Ideal for commercial premises, offices, hotels, etc.



Efficiency

A++ rating in cooling and A+ in heating.




MUTE mode

The console is set to AUTO mode and the indoor unit operates at minimum speed: 32dB.



ECO mode

It allows energy savings in both heating and cooling.



Better air distribution

The console has 2 air outlets (top and bottom) that help to distribute the air better and improve the room's climate.



CONSOLE 1x1 INSPIRA



MODELS		IU	OU
EAN CODE			
Power supply / Connection		V,Ph,Hz	220~240V (1 Phase ~ 50Hz) Outdoor unit
PERFORMANCE			
Cooling power	Power	kW	3.400 (1.000~3.770)
		Btu/h	11600 (3410~12860)
	Consumption	W	1130 (290~1500)
	SEER	-	6.1
Energy classification		Cooling	A++
Heating power	Power	kW	3.420 (1.000~3.810)
		Btu/h	11670 (3410~13000)
	Consumption	W	922 (290~1720)
	SCOP	-	4.0
Energy classification		Heating	A+
FEATURES			
Indoor unit	Sound power	dB(A)	52
	Sound pressure	dB(A)	42
	Air flow rate	m3/h	650 / 620 / 570 / 540 / 520
	Selectable temperature range	°C	17-32 / 0-30
Outdoor unit	Sound power	dB(A)	60
	Air flow rate	m3/h	1900
	Operating temp. cooling / heating	°C	-15-53 / -20-30
	Compressor	-	GMCC
Refrigerant	Type / Load	R32/Kg	0.55kg
	Additional liquid load > 5 m	g/m	15
DIMENSIONS AND WEIGHT			
Indoor unit	Net dimensions (W x H x D)	mm	700x600x215
	Gross dimensions (W x H x D)	mm	775x725x280
	Net / Gross weight	Kg	16 / 18
Outdoor unit	Net dimensions (W x H x D)	mm	777x498x290
	Gross dimensions (W x H x D)	mm	818x520x325
	Net / Gross weight	Kg	24 / 26
CONNECTIONS			
Refrigeration pipe	Liquid - Gas	Inch	1/4" - 3/8"
	Max. length	m	25
	Max. unevenness	m	10
Electrical connections	Internal supply	mm	with the communication
	External supply	mm	2 x 1.5 + T
	Interconnection (shielded)	mm	3 x 0.75 + T