



PORTABLE AIR CONDITIONING P41

R-290



Easy to transport



LED Display



Easy installation and maintenance



Dehumidifier



Remote control



Window kit included



Mode cooling / heating



24h timer

MODEL

HTW-PC-020P41	HTW-PC-026P41	HTW-PB-026P41	HTW-PC-035P41	HTW-PB-035P41
8435483866805	8435483866829	8435483866812	8435483866843	8435483866836

Power supply	V,F,HZ	220-240V (1 Phase ~ 50Hz)
--------------	--------	---------------------------

PERFORMANCE

Cooling capacity	Capacity	kW	2	2,6	2,6	3,5	3,5
	Consumption	W	785	1000	1000	1346	1346
	Current	A	3,5	4,5	4,5	5,9	5,9
	EER	W/W	2,6	2,6	2,6	2,6	2,6
	Energy Classification	Cooling	A	A	A	A	A
Heating capacity	Capacity	kW			2,4		3,2
	Consumption	W			1043		1391
	Current	A			4,7		6,3
	COP	W/W			2,3		2,3
	Energy Classification	Heat			A		A

CHARACTERISTICS

Sound power	dB(A)	65	65	65	65	65
Sound pressure	dB(A)	55	55	55	55	55
Air flow rate	m3/h	300	300	300	300	300
Air-conditioned perimeter (depending on room conditions)	m ²	10~16	12~18	12~18	14~20	14~20
Operation temperature	°C	18-35	18-35	18-35	18-35	18-35
Selectable temperature	°C	16-31	16-31	16-31	16-31	16-31
Refrigerant	Type	R290	R290	R290	R290	R290
	Charge quantity	Kg	0,08	0,14	0,14	0,185

DIMENSIONS AND WEIGHT

Net dimensions (WxHxD)	mm	285x698x 335	285x698x 335	285x698x 335	285x698x 335	285x698x 335
Gross Dimensions (WxHxD)		340x885x 390	340x885x 390	340x885x 390	340x885x 390	340x885x 390
Net weight	Kg	19	20	20	24	24

CONNECTIONS

Length of exhaust duct	mm	1500	1500	1500	1500	1500
Diameter of exhaust duct	mm	150	150	150	165	165
Cable length	mm	1800	1800	1800	1800	1800

*According to model