



SPLIT 1X1 IX75



Golden Fin
protection

24 Hour timer

Silent mode

Auto-
restart

Función
I Feel

Turbo button

MODELS		INT.	HTWS026IX75	HTWS035IX75	HTWS052IX75	HTWS071IX75
		EXT.	HTWS026IX75-INT	HTWS035IX75-INT	HTWS052IX75-INT	HTWS071IX75-INT
			HTWS026IX75-EXT	HTWS035IX75-EXT	HTWS052IX75-EXT	HTWS071IX75-EXT
EAN CODE			8435483847187	8435483847217	8435483847248	8435483847279
Power supply		V,Ph,Hz	220~240V (1 Phase ~ 50Hz)			
PERFORMANCE						
Cooling capacity	Capacity	W	2500(660-2780)	3500(660-3700)	5000(1610-5200)	7100 (1110-7800)
		Frig/h	2150 (568 - 2520)	3000 (568 - 3270)	4470 (1385 - 4660)	6100 (955 - 6700)
	Consumption	W	770(250-1300)	1190(250-1600)	1540(350-2400)	2400(450-3350)
	Power	A	3.6 (1,1 - 8,8)	5,5 (1,1 - 9,6)	7,2 (1,6 - 10,4)	11,1 (2,1 - 16,4)
	SEER	—	6,1	6,1	6,1	6,1
	Energy rating	Cold	A++	A++	A++	A++
	Anual Consumption	kWh	138	175	271	321
	EER	W/W	3,25	2,94	3,25	2,96
Heating capacity	Capacity	W	2600(660-2880)	3500(660-3800)	5000(1610-5300)	7100 (1370-8200)
		cal/h	2236 (568 - 2640)	3000 (568 - 3400)	4470 (1385 - 4782)	6100 (1178 - 7052)
	Consumption	W	690(250-1300)	950(250-1600)	1340(350-2450)	2200 (450-3350)
	power	A	3.2 (1,1 - 9,0)	4,4 (1,1 - 10,0)	6,2 (1,6 - 10,6)	10,1 (2,1 - 16,8)
	SCOP	—	4	4	4	4
	Energy rating	Heat	A+	A+	A+	A+
	Anual Consumption	kWh	525	652	1007	1279
	COP	W/W	3,77	3,68	3,73	3,23
FEATURES						
Indoor unit	Sound power	dB(A)	50/47/44/37	52/48/43/37	56/51/48/44	59/54/51/44
	Sound pressure	dB(A)	40/38/34/21	42/38/34/23	44/41/38/24	46/43/40/24
	Air flow rate	m3/h	500/450/400/350	550/500/450/400	820/720/620/520	1200/1050/900/800
	Capacity of dehumidification	L/h	0,9	1,1	1,4	2,2
	Temperature range	°C	16 - 32	16 - 32	16 - 32	16 - 32
Outdoor unit	Sound power	dB(A)	62	64	65	65
	Sound pressure	dB(A)	52	52	54	55
	Air flow rate	m3/h	1650	1650	2300	2850
	Operating temperature cold/heat	°C	-15~53	-15~53	-15~53	-15~53
	Compressor		GMCC	GMCC	GMCC	SANYO
Refrigerant	Type/Charge	R32/kg	0,57	0,6	0,95	1,5
	Additional load >5	g/m	15	15	15	15
DIMENSIONS AND WEIGHT						
Unidad interior	Net dimensions (WxHxD)	mm	700 x 270 x 197	805 x 270 x 197	908 x 295 x 225	1025 x 319 x 223
	Gross dimensions (WxHxDxD)	mm	750 x 317 x 267	864 x 331 x 265	979 x 354 x 292	1102 x 395 x 305
	Net / Gross weight	kg	7/8	7,5/8,5	10/12	13/15
Unidad exterior	Net dimensions (WxHxD)	mm	665 x 530 x 260	665 x 530 x 260	780 x 560 x 270	820 x 635 x 310
	Gross dimensions (WxHxDxD)	mm	785 x 600 x 340	768 x 570 x 324	889 x 612 x 359	969 x 688 x 402
	Net / Gross weight	kg	21,2/24,3	22,9/26,2	27,6/30,6	36,7/40,7
CONNECTIONS						
Tubería frigorífica	Liquid - Gas	in.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
	Max. length	m	20	20	25	25
	Max. Elevation	m	15	15	15	15
Conexiones eléctricas	Power supply	mm	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T
	Interconnection	mm	4 x 1,5 + T	4 x 1,5 + T	4 x 1,5 + T	4 x 1,5 + T

Notes: Capacity data under standard conditions. Actual data will vary depending on installation location and use.

Sound pressure values are measured at a distance of 1m in a semi-anechoic chamber.

The dimensions of the electrical wiring are approximate and should be calculated according to the conditions of the installation itself.

HTW, a Gia Group company.