

HTW

QUALITY COMFORT EVERYWHERE

HOME RANGE

3 ANOS
GARANTIA
TOTAL
COMPROMISSO DE QUALIDADE

5 YEARS
WARRANTY
COMPRESSOR
QUALITY COMMITMENT

21dB
DEPENDENT ON MODEL

A+++
SEER

A+
SCOP

A+++
SCOP
Warmer

Data sheet

SPLIT 1X1 EON



MODELOS		INT.	HTW-S026EON-R32	HTW-S035EON-R32	HTW-S052EON-R32
		EXT.	HTW-S026EON-R32-I	HTW-S035EON-R32-I	HTW-S052EON-R32-I
CÓDE EAN			HTW-S026EON-R32-O	HTW-S035EON-R32-O	HTW-S052EON-R32-O
Electrical power supply		V,F,Hz	8435483847026	8435483847033	8435483847040
PERFORMANCE					
Cooling capacity	Capacity	kW	2,6 (0,66~3,30)	3,5 (0,66~3,80)	5,2 (1,61~6,20)
		Btu/h	9000 (2250~11300)	12000 (2250~13000)	18000 (5500~21200)
	Consumption	W	580 (250~1300)	950 (250~1600)	1400 (350~2400)
	Current	A	2,7(1,1-8,8)	4,4(1,1-9,6)	6,5(1,6-12,2)
	SEER	W/W	8,5	8,5	8,5
	EER	W/W	4,48	3,68	3,71
	Energy class	-	A+++	A+++	A+++
Heating capacity	Annual consumption	kWh	96	130	210
	Capacidad	kW	2,6 (0,66~3,60)	3,5 (0,66~4,00)	5,2 (1,61~6,20)
		Btu/h	9000 (2250~12300)	12000 (2250~13700)	18000 (5500~21200)
	Consumo	W	620 (250~1300)	920 (250~1600)	1350 (350~2450)
	Corriente	A	2,9(1,1-9,0)	4,3(1,2-10,0)	6,3(1,6-12,8)
	SCOP	W/W	4,6	4,6	4,6
	COP	W/W	4,2	3,7	3,7
Heating capacity	Clasificación energética	-	A++	A++	A++
	Consumo anual	kWh	670	770	1280
CHARACTERISTICS					
Heating capacity	Sound power (H/M/L/S)	dB	52/48/43/37	52/48/43/37	59/54/51/44
	Sound pressure (H/M/L/S)	dB	40/38/34/21	42/38/34/23	44/41/38/24
	Air flow (H/M/L/S)	m³/h	550/500/450/400	550/500/450/400	1200/1050/900/800
Outdoor unit	Temperature range, seleccionable	°C	16-32	16-32	16-32
	Sound power	dB	62	64	65
	Sound pressure	dB	50	52	56
	Air flow	m³/h	2300	2300	2300
	Operating temperature	°C	-15-30/16-53	-15-30/16-53	-15-30/16-53
	Compressor	Tipo	Rotary	Rotary	Rotary
		Marca	GMCC	GMCC	SANYO
Refrigerant	Type/Charge	R32/kg	0,62	0,64	1,1
	Carga adicional	g/m	15	15	15
DIMENSIONS AND WEIGHT					
Indoor unit	Net dimensions (W×H×D)	mm	805x270x197	805x270x197	1025x319x223
	Gross dimensions (W×H×D)	mm	864x332x265	864x332x265	1102x395x305
	Net/Gross weight	kg	7,5/9	7,5/9	12/15
Outdoor unit	Net dimensions (W×H×D)	mm	780x560x270	780x560x270	780x560x270
	Gross dimensions (W×H×D)	mm	889x612x359	889x612x359	889x612x359
	Net/Gross weight	kg	25,3/28,3	25,3/28,3	25,3/28,3
CONNECTIONS					
Refrigeration pipe	Liquid - Gas	Pulg.	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"
	Max. length	m	20	20	20
	Max. elevation	m	15	15	15
Electric connections	Power supply	mm	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T
	Interconnection	mm	3 x 2,5 + T	3 x 2,5 + T	3 x 2,5 + T

Notes:

Capacity data in standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.

The dimensions of the electrical wiring are approximate, they should be calculated according to the conditions of the installation itself.