



SPLIT 1X1 IX75B



Golden Fin protection

24 Hour timer

Silent mode

Auto-restart

Función I Feel

Turbo button

MODELS	INT.	HTWS026IX75B	HTWS035IX75B	HTWS052IX75B	HTWS071IX75B	
		HTWS026IX75B-INT	HTWS035IX75B-INT	HTWS052IX75B-INT	HTWS071IX75B-INT	
EXT.		HTWS026IX75B-EXT	HTWS035IX75B-EXT	HTWS052IX75B-EXT	HTWS071IX75B-EXT	
EAN CODE		8435483869479	8435483869509	8435483869530	8435483869561	
Power supply	V,Ph,Hz	220~240V (1 Phase ~ 50Hz)				
PERFORMANCE						
Cooling capacity	Capacity	kW	2,6 (0,66~2,78)	3,5 (0,66~3,70)	5,2 (1,61~5,20)	7,1 (1,11~7,80)
		Btu/h	8866 (2250~9479)	11935 (2250~12617)	17732 (5490 ~ 17732)	24211 (3785~26598)
	Consumption	W	770 (250~1300)	1190 (250~1600)	1540 (350~2400)	2400 (450~3350)
	Current	A	3,6 (1,1~8,8)	5,5 (1,1~9,6)	7,2 (1,6~12,2)	11,1 (2,1~16,4)
	SEER	-	6,1	6,1	6,1	6,1
	Energy class	-	A++	A++	A++	A++
Annual consumption	kWh	138	175	271	321	
Heating capacity	Capacity	kW	2,6 (0,66~2,88)	3,5 (0,66~3,80)	5,0 (1,61~5,30)	7,1 (1,37~8,20)
		Btu/h	8866 (2250~9821)	11935 (2250~12958)	17050 (5490~18073)	24211 (4672~27962)
	Consumption	W	690 (250~1300)	950 (250~1600)	1340 (350~2450)	2200 (450~3350)
	Current	A	3,2 (1,1~9,0)	4,4 (1,1~10,0)	6,2 (1,6~10,6)	10,1 (2,1~16,8)
	SCOP	W/W	4,0	4,0	4,0	4,0
	Energy class	-	A+	A+	A+	A+
Annual consumption	kWh	701	842	1304	1677	
FEATURES						
Indoor unit	Sound power (H/M/L/S)	dB	50/47/44/37	52/48/43/37	56/51/48/44	59/54/51/44
	Sound pressure (H/M/L/S)	dB	40/38/34/21	42/38/34/23	44/41/38/24	46/43/40/24
	Air flow (H/M/L/S)	m³/h	500/450/400/350	550/500/450/400	820/720/620/520	1200/1050/900/800
	Operating temperature (Cold/Heat)	°C	17~32	17~32	17~32	17~32
Outdoor unit	Sound power	dB	62	64	65	65
	Sound pressure	dB	52	52	54	55
	Air flow	m³/h	1650	1650	2300	2850
	Operating temperature (Cold/Heat)	°C	-15~53	-15~53	-15~53	-15~53
Refrigerant	Type/Charge	R32/kg	0,60	0,63	1,00	1,40
	Carga adicional	g/m	15	15	15	15
DIMENSIONS AND WEIGHT						
Indoor unit	Net dimensions (WxHxD)	mm	700x270x197	805x270x197	908x295x225	1025x319x223
	Gross dimensions (WxHxD)	mm	750x317x256	864x332x265	979x354x292	1102x395x305
	Net/Gross weight	kg	7/8	7,5/8,5	10/12	12,6/15,0
Outdoor unit	Net dimensions (WxHxD)	mm	665x530x260	665x530x260	780x560x270	820x635x310
	Gross dimensions (WxHxD)	mm	768x570x326	768x570x326	889x612x359	969x688x402
	Net/Gross weight	kg	21,2/24,3	22,8/26,2	27,6/30,6	36,7/40,7
CONNECTIONS						
Refrigeration pipe	Liquid - Gas	in.	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	3/8 - 5/8
	Max. length	m	20	20	25	25
	Max. elevation	m	15	15	15	15
Electric connections	Power supply	mm	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T
	Interconnection	mm	4 x 1,5 + T	4 x 1,5 + T	4 x 1,5 + T	4 x 1,5 + T

HTW reserves the right to modify models and technical data without prior notice. Information is valid except in the case of typographical or printing errors.

Notes: Capacity data under standard conditions. Actual data will vary depending on installation location and use.

Sound pressure values are measured at a distance of 1m in a semi-anechoic chamber.

The dimensions of the electrical wiring are approximate and should be calculated according to the conditions of the installation itself.